
















订货信息

订货号	LZ	PG
EMB8000 24 A – 0102	680324-0102	●
应用: 排烟排热系统模块化控制箱 EMB8000, 工厂组装和接线		
	技术参数 (额定值) 操作电压: 230 V AC (195 – 253 V AC, 50/60 Hz) 额定功率: 576 W 输出电压: 24 V DC (20 – 28 V DC / 0,5 Vpp) 输出电流: 24 A 连接和功能: 详见具体的模块 外壳: 明装, 钢制, RAL 7035 (浅灰色) 尺寸 (WxHxD): 600 x 600 x 250 mm	
	排烟组: 1 (1 CM) 通风组: 2 (2DM) 备用电池: 2 x 12 V / 17 Ah (订购号 543000) VdS证书号: G 512005	
模块顺序		
EMB8000 24 A – 0103	680324-0103	●
排烟组: 1 (1 CM) 通风组: 3 (3 DM) 备用电池: 2 x 12 V / 17 Ah (订购号543000)		
模块顺序		
EMB8000 24 A – 0104	680324-0104	●
排烟组: 1 (1 CM) 通风组: 4 (4 DM) 备用电池: 2 x 12 V / 17 Ah (订购号543000)		
模块顺序		
EMB8000 24 A – 0105	680324-0105	●
排烟组: 1 (1 CM) 通风组: 5 (5 DM) 备用电池: 2 x 12 V / 17 Ah (订购号 543000)		
模块顺序		
EMB8000 24 A – 0106	680324-0106	●
排烟组: 1 (1 CM) 通风组: 6 (6 DM) 备用电池: 2 x 12 V / 17 Ah (订购号543000)		
模块顺序		
EMB8000 24 A – 0109	680324-0109	●
排烟组: 1 (1 CM) 通风组: 9 (9 DM) 备用电池: 2 x 12 V / 17 Ah (订购号 543000)		
模块顺序		

订货信息

订货号	LZ	PG
EMB8000 24 A – 0202	680324-0202	●
应用: 排烟排热系统模块化控制箱EMB8000, 工厂组装和接线		
	技术参数 (额定值) 操作电压: 230 V AC (195 – 253 V AC, 50/60 Hz) 额定功率: 576 W 输出电压: 24 V DC (20 – 28 V DC / 0,5 Vpp) 输出电流: 24 A 连接和功能: 详见具体的模块 外壳: 明装, 钢制, RAL 7035 (浅灰色) 尺寸 (WxHxD): 600 x 600 x 250 mm	
	排烟组: 2 (1 CM + 1 SM) 通风组: 2 (2 DM) 备用电池: 2 x 12 V / 17 Ah (订购号 543000) VdS证书号: G 512005	
模块顺序		
EMB8000 24 A – 0203	680324-0203	●
	排烟组: 2 (1 CM + 1 SM) 通风组: 3 (3 DM) 备用电池: 2 x 12 V / 17 Ah (订购号543000)	
模块顺序		
EMB8000 24 A – 0204	680324-0204	●
	排烟组: 2 (1 CM + 1 SM) 通风组: 4 (4 DM) 备用电池: 2 x 12 V / 17 Ah (订购号543000)	
模块顺序		
EMB8000 24 A – 0205	680324-0205	●
	排烟组: 2 (1 CM + 1 SM) 通风组: 5 (5 DM) 备用电池: 2 x 12 V / 17 Ah (订购号543000)	
模块顺序		
EMB8000 24 A – 0206	680324-0206	●
	排烟组: 2 (1 CM + 1 SM) 通风组: 6 (6 DM) 备用电池: 2 x 12 V / 17 Ah (订购号543000)	
模块顺序		
EMB8000 24 A – 0208	680324-0208	●
	排烟组: 2 (1 CM + 1 SM) 通风组: 8 (8 DM) 备用电池: 2 x 12 V / 24 Ah (订购号544000)	
模块顺序		

订货信息

订货号	LZ	PG
EMB8000 24 A - 0303	680324-0303	●
应用: 排烟排热系统模块化控制箱MB8000, 工厂组装和接线		
	技术参数 (额定值) 操作电压: 230 V AC (195 - 253 V AC, 50/60 Hz) 额定功率: 576 W 输出电压: 24 V DC (20 - 28 V DC / 0,5 Vpp) 输出电流: 24 A 连接和功能: 详见具体的模块 外壳: 明装, 钢制, RAL 7035 (浅灰色) 尺寸 (WxHxD): 600 x 600 x 250 mm 排烟组: 1 (1 CM+2SM) 通风组: 3 (3DM) 备用电池: 2 x 12 V / 24 Ah (订购号 544000) VdS证书号: G 512005	
模块顺序	PM - CM - 1xDM - SM - 1xDM - SM - 1xDM	
EMB8000 24 A - 0304	680324-0304	●
	排烟组: 3 (1 CM + 2 SM) 通风组: 4 (4 DM) 备用电池: 2 x 12 V / 24 Ah (订购号 544000)	
模块顺序	PM - CM - 2xDM - SM - 1xDM - SM - 1xDM max. 20 A max. 20 A	
EMB8000 24 A - 0305	680324-0305	●
	排烟组: 3 (1 CM + 2 SM) 通风组: 5 (5 DM) 备用电池: 2 x 12 V / 24 Ah (订购号544000)	
模块顺序	PM - CM - 2xDM - SM - 2xDM - SM - 1xDM	
EMB8000 24 A - 0309	680324-0309	●
	排烟组: 3 (1 CM + 2 SM) 通风组: 9 (9 DM) 备用电池: 2 x 12 V / 24 Ah (订购号 544000)	
模块顺序	PM - CM - 3xDM - SM - 3xDM - SM - 3xDM	
EMB8000 24 A - 0404	680324-0404	●
	排烟组: 4 (1 CM + 3 SM) 通风组: 4 (4 DM) 备用电池: 2 x 12 V / 24 Ah (订购号544000)	
模块顺序	PM - CM - 1xDM - SM - 1xDM - SM - 1xDM - SM - 1xDM	
EMB8000 24 A - 0406	680324-0406	●
	排烟组: 4 (1 CM + 3 SM) 通风组: 6 (6 DM) 备用电池: 2 x 12 V / 24 Ah (订购号544000)	
模块顺序	PM - CM - 2xDM - SM - 2xDM - SM - 1xDM - SM - 1xDM	